8CH Face Recognition NVR

NVR8-8200FA

8MP





MODEL			NVR8-8200FA
Video		Input	8CH Over Network
		Output	HDMI (4K@60Hz, 4K@30Hz, 1080P), VGA (1080P, 1280x1024, 1024x768)
		Decoding Format	H.265 (HEVC) / H.264
		Decoding Capabilities	1Ch - 8MP ; 4Ch - 2x8MP + 2x5MP ; 9Ch - 1MP
		Analytics Channels	8Ch (Requires supporting IPC)
Analytics		Supported Analytics	Face Recognition, Smart Search, Camera Tampering, Line Crossing (Old + DDA), Sterile Area (Old + DDA), Object Counting (Old + DDA), Item Monitoring, Crowd Gathering
		Face Recognition Rate	240 Faces per minute (All Channels) / 5 Faces per second (Single Channel)
Audio		Input	1CH + Depends on Camera Inputs
		Output	1CH + Depends on Camera Outputs
		Two Way Audio	Yes
Bandwidth		Incoming	80Mbps
		Outgoing	80Mbps
Record / Remote App.	Record/ Main Stream	Real-Time Recording	8CH 8MP Real-Time
		8MP	480FPS (NTSC)/400FPS (PAL)
		5MP and lower	480FPS (NTSC)/400FPS (PAL)
		Master Streams over Network	Up to 12CH@Recording Resolution
	Sub Stream	Resolution	Depends on IPC
		Sub-Streams over Network	Up to Outgoing Bandwidth Capacity
	General	User Access	10 Users Online with Professional Autorithy Management
		Recording Modes	Schedule, Manual, Motion, Sensor, Analytics
		Applications	Provision Cam2 for iOS/Android, IE for Windows 7/8/10, Safari for Mac OS, CMS for Windows/MAC
Playback		Playback (Local / Remote)	8Ch / 8Ch
		Search Mode	Smart Search, Face Recognition, Time-Slice, Time, Event, POS, File Management
Backup		USB	1 USB 2.0 Port + 1 USB 3.0 Port
		Backup Format	AVI/DAT
Alarm		Input	8 + Depends on Camera
		Output	4 + Depends on Camera
Storage		HDD	1 SATA (8TB Max)
		E-SATA	No
		RAID	Not Supported
PTZ		Connection	Via Network
		Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus
		RS-485	Yes (C06 Keyboard Connection)
Network		Ethernet	1000 Mbps (RJ-45)
		Protocols	TCP/IP, DHCP, DDNS, NTP, SMTP, P2P, RTSP, FTP, HTTPS, 802.1X, SNMP, NAT
		ONVIF	Yes (For IP Channels)
PoE		Ports	No
		Interface	No
		Standard	No
		Total Power	No
		Max. Power Output (Per Ch.)	No
Others		Power Supply	DC12V/2A
		Power Consumption (No HDD)	10W
		Dimention	W375xD275xH50mm
		Operation Temperature	0°C ~50°C