

GLKD-I V.1.0

- Support 1xDDR4 2400 MHz up to 8GB
- Applied all solid Capacitors
- Applied ESD Protection
- Realtek RTL8111H Gigabit LAN Chip
- Support 2230 WIFI/BT
- Support 2242/2280 SSD
- Amplifier IC ALC 105 + 4-pin Speaker header
- Support Windows 10




Support Windows 10
Support the latest Windows 10 technology which provides touch-enabled control, Apps and can connect with the cloud to connect with your files, photos, people and settings, wherever you sign in.



Single DDR4 2400
Expands the bandwidth of your system memory up to 19.2GB/s.



Support SATA 6G
Supporting SATA 6Gbps that has wider bandwidth by providing much faster data transfer rate than SATA 3Gbps.



Support super-speed USB 3.0
Interface technology which delivers 10X the data transfer rate.



Gigabit LAN
Delivers transfer speeds 10X faster than traditional 10/1000 Ethernet. Ideal for large network data transfer.



Onboard Video -HDMI Output
HDMI interface supports existing high-definition video formats(720p, 1080i, and even 1080p), plus multi-channel digital audio on a single cable



EZ Graphical BIOS Utility
User Friendly GUI UEFI BIOS lets you modify and update your BIOS with your mouse and an easy to understand layout.

SPECIFICATIONS

CPU	BGA 1090 Gemini Lake SoC (J4025/J4125/J5040) 1 Phase Thermal Design Power (TDP 10W)
Memory	Single Channel DDR4 2400MHz
Expansion slot	1 x 2242/2280 M.2 Slot Support SATA SSD (for Opt.) 1 x 2230 M.2 Slot Support Wifi/BT and Intel® CNVi (for Opt.)
Storage	2 x Serial ATA 6Gb/s devices (SATA2 share with M.2 SSD)
Audio	Realtek ALC662 6-Channel High Definition Audio Codec Realtek ACL105 Amplifier (For Opt.)
LAN	Realtek RTL8111H Gigabit LAN
Rear Panel I/O	1 x PS/2 Keyboard + Mouse 1 x HDMI Port 1 x VGA Port or 1x DP Port (for Opt.) 4 x USB 3.0 ports 2 x USB 2.0 ports 1 x RJ45 Port 1 x Audio Jack (Line-Out / MIC) 1 x DC- IN 19V Adapter
Internal I/O	1 x 4-pin SYS_FAN connector
Connectors & Headers	1 x Amplifier Speaker Header 4-PIN (for Opt.) 2 x USB 2.0 headers 1 x SATA Power header 1 x LPT header 2 x COM headers 1 x Front Panel header 1 x Front Audio header
System BIOS	AMI BIOS with 128Mb SPI Flash ROM
Other Functions	All Solid Capacitors
Form Factor	Mini-ITX:170 *170 mm