



Archer T3U Plus



CARACTERÍSTICAS DE HARDWARE

Interface	USB 3.0
LED	Status

Dimensiones	2.28 × 0.71 × 6.83 in (57.8 × 18 × 173.4 mm)
Antena	2 External High Gain Antennas

CARACTERÍSTICAS INALÁMBRICAS

Estándares Inalámbricos	IEEE 802.11b/g/n 2.4 GHz, IEEE 802.11a/n/ac 5 GHz
Tasa de Señal	5 GHz:

11ac: Up to 867 Mbps(dynamic)

11n: Up to 300 Mbps(dynamic)

11a: Up to 54 Mbps(dynamic)

2.4 GHz:

11n: Up to 400 Mbps(dynamic)

11g: Up to 54 Mbps(dynamic)

11b: Up to 11 Mbps(dynamic)

Sensibilidad de Recepción

5 GHz:

11ac VHT80: -62dBm

11ac VHT40: -64dBm

11ac VHT20: -68dBm

11n HT40: -71dBm

11n HT20: -73dBm

11a 54Mbps: -77dBm

2.4 GHz:

11n HT40: -70dBm

11n HT20: -71dBm

11g 54Mbps: -73dBm

11b 11Mbps: -87dBm

Potencia de Transmision

5 GHz: 20dBm(FCC) / 20dBm(CE) (EIRP)

2.4 GHz : 18dBm(FCC) / 18dBm(CE) (EIRP)

Modos Inalámbricos

Infrastructure mode

Seguridad Inalámbrica

WEP, WPA/WPA2, WPA-PSK/WPA2-PSK

OTROS

Certificacion	FCC, CE, RoHS
Contenidos del Paquete	AC1300 High Gain Wireless Dual Band USB Adapter Quick Installation Guide Resource CD
Requisitos del Sistema	Windows 10/8.1/8/7 (32/64 bit)
Ambiente	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing