



TL-SF1008P

CARACTERÍSTICAS DE HARDWARE

Interface

8 10/100Mbps RJ45 Ports
AUTO Negotiation/AUTO MDI/MDIX

Medios de Red

10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)
EIA/TIA-568 100Ω STP (maximum 100m)

Cantidad de Ventiladores

Fanless

Cerradura de Seguridad Física

Yes

Consumo de Energía

Maximum (PoE on): 60.2W (220V/50Hz)

Maximum (PoE off): 3.2W (220V/50Hz)

Fuente de Alimentación Externa

External Power Adapter(Output: 48VDC / 1.25A)

Tasa de Reenvío de Paquete

1.1904 Mpps

Puertos PoE (RJ45)

Standard: 802.3 af compliant

PoE Ports: Port1- Port4

Power Supply: 57W

Sitio de Banda Ancha

1.6Gbps

Tabla de Dirección Mac

2K

Jumbo Frame

2 KB

Capacidad de Switcheo

1.6 Gbps

Dimensiones (W X D X H)

6.7*3.9*1.1 in. (171*98*27 mm)

Consumo Máximo de energía

2.27 W (220 V/ 50 Hz. no PD connected)

75.33 W (220 V/ 50 Hz. with 66 W PD connected)

Disipación Máxima de Calor

7.74 BTU/h(no PD connected)

256.88 BTU/h(with 66 W PD connected)

CARACTERÍSTICAS DE SOFTWARE

Método de Transmisión

Store-And-Forward

Funciones Avanzadas

Compatible With IEEE 802.3af Compliant PDs

Priority Function

Mac Address Auto-Learning And Auto-Aging

IEEE802.3x Flow Control For Full-Duplex Mode And
Backpressure For Half-Duplex Mode

OTROS

Certificacion

FCC, CE, RoHS

Contenidos del Paquete

TL-SF1008P, Power Adapter, User Guide

Consumo

2.3 watts (max. no PD connected)

59.3 watts (max. with 57w PD connected)

Ambiente

Operating Temperature: 0°C~40°C (32°F~104°F)

Storage Temperature: -40°C~70°C (-40°F~158°F)

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing