



OC200

CARACTERÍSTICAS DE HARDWARE

Interface

10/100Mbps Ethernet Port*2

USB 2.0 Port*1

Micro USB Port*1

Fuente de Alimentación

802.3af/at PoE or Micro USB (DC 5V/Minimum 1A)

Dimensiones

3.9×3.9×1.0in. (100×98×25mm)

CARACTERÍSTICAS

Función inalámbrica

L3 Management

Multi-SSID

Load Balance

Band Steering

Airtime Fairness

Beamforming

Rate Limit

Wireless Schedule

QoS

Seguridad inalámbrica

Captive Portal Authentication

Access Control

Wireless Mac Address Filtering

Wireless Isolation Between Clients

SSID to VLAN Mapping

Rogue AP Detection

AP Management

Automatic Discovery

Unified Configuration

Reboot Schedule

Batch Firmware Upgrade

LED ON/OFF

Captive Portal

Authentication

ADMINISTRACIÓN

Omada App

Yes

Centralized Management

Up to 100 Omada access points, JetStream switches, and

SafeStream routers

Cloud Access

Yes

L3 Management	Yes
Multi-site Management	Yes
Management Features	• Automatic Device Discovery • Batch Configuration • Batch Firmware Upgrading • Intelligent Network Monitoring • Abnormal Event Warnings • Unified Configuration • Reboot Schedule • Captive Portal Configuration
OTROS	
Certificacion	CE, FCC, RoHS
Contenidos del Paquete	Omada Cloud Controller OC200 Quick Installation Guide Ethernet Cable
Requisitos del Sistema	Microsoft® Windows®10, 8, 7,Vista™, XP or MAC® OS,
Ambiente	NetWare®, UNIX® or Linux Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing