



TL-SF1006P



CARACTERÍSTICAS DE HARDWARE

Interface	• 6× 10/100 Mbps RJ45 Ports (ports 1–4 support 802.3af/at PoE+) • AUTO Negotiation • AUTO MDI/MDIX
Medios de Red	• 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) • EIA/TIA-568 100Ω STP (maximum 100m) • 100BASE-TX: UTP category 5, 5e cable (maximum 100m) • EIA/TIA-568 100Ω STP (maximum 100m)
Cantidad de Ventiladores	Fanless
Cerradura de Seguridad Física	Yes
Fuente de Alimentación Externa	External Power Adapter (Output: 53.5 V DC / 1.31 A)
Tasa de Reenvío de Paquete	0.8928 Mpps
Puertos PoE (RJ45)	• Standard: 802.3 af/at compliant • PoE Ports: Ports 1–4 • Power Supply: 67 W
Tabla de Dirección Mac	2K
Jumbo Frame	2 KB
Capacidad de Switcheo	1.2 Gbps
Dimensiones (W X D X H)	6.2 x 4.0 x 1.0 in (158 x 101 x 25 mm)
Consumo Máximo de energía	• 1.9 W (220 V / 50 Hz, no PD connected) • 74 W (220 V / 50 Hz, with 67 W PD connected)
Disipación Máxima de Calor	• 6.48 BTU/h(no PD connected) • 252.34 BTU/h(with 67 W PD connected)

CARACTERÍSTICAS DE SOFTWARE

Método de Transmisión	Store-And-Forward
Funciones Avanzadas	• Compatible With IEEE 802.3af/at Compliant PDs • Extend Mode Button (Ports 1–4) • Priority Mode Button (Ports 1–2) • Mac Address Auto-Learning and Auto-Aging

- IEEE802.3x Flow Control For Full-Duplex Mode and Backpressure for Half-Duplex Mode

OTROS

Certificacion

Contenidos del Paquete

FCC, CE, RoHS

- TL-SF1006P
- Power Adapter
- Installation Guide

Ambiente

- Operating Temperature: 0–40 °C (32–104 °F)
- Storage Temperature: -40–70 °C (-40–158 °F)
- Operating Humidity: 10–90% RH non-condensing
- Storage Humidity: 5–90% RH non-condensing