



EAP265 HD

CARACTERÍSTICAS DE HARDWARE

Interface

Cerradura de Seguridad Física

Botón

Fuente de Alimentación

2 × Gigabit Ethernet (RJ-45) Port (One port supports IEEE802.3af/at PoE and Passive PoE)

Yes

Reset

- 802.3af/at PoE

Consumo de Energía

Dimensiones (W X D X H)

Tipo de Antena

- 48V Passive PoE (+4,5pins; -7,8pins. PoE Adapter Included)

12.3 W

8.1 × 7.1 × 1.5 in (205.5 × 181.5 × 37.1 mm)

Internal Omni

- 2.4 GHz: 3× 3.5 dBi

- 5 GHz: 3× 4 dBi

Ceiling /Wall Mounting (Kits included)

Montaje

CARACTERÍSTICAS INALÁMBRICAS

Estándares Inalámbricos

Frecuencia

Tasa de Señal

IEEE 802.11ac/n/g/b/a

2.4GHz and 5GHz

- 5 GHz: Up to 1300 Mbps

- 2.4 GHz: Up to 450 Mbps

- Multiple SSIDs (Up to 16 SSIDs, 8 for each band)

- Enable/Disable Wireless Radio

- Automatic Channel Assignment

Funciones Inalámbricas

- Transmit Power Control (Adjust Transmit Power on dBm)

- QoS(WMM)

- MU-MIMO

- Seamless Roaming

- Band Steering

- Load Balance

- Airtime Fairness

- Beamforming

- Rate Limit

- Reboot Schedule

Seguridad Inalámbrica	• Wireless Schedule • Wireless Statistics based on SSID/AP/Client • Captive Portal Authentication • Access Control • Wireless Mac Address Filtering • Wireless Isolation Between Clients • SSID to VLAN Mapping • Rogue AP Detection • 802.1X Support • 64/128/152-bit WEP / WPA / WPA2-Enterprise, WPA-PSK / WPA2-PSK
Potencia de Transmisión	• CE : ≤20 dBm (2.4 GHz) ≤23 dBm (5 GHz) • FCC: ≤24 dBm (2.4 GHz) ≤24 dBm (5 GHz)
ADMINISTRACIÓN	
Omada App	Yes
Centralized Management	• Omada Cloud-Based Controller • Omada Hardware Controller (OC300) • Omada Hardware Controller (OC200) • Omada Software Controller
Cloud Access	Yes (Through OC300, OC200, Omada Cloud-Based Controller, or Omada Software Controller)
Alertas de Correo Electrónico	Yes
LED ON/OFF Control	Yes
Management MAC Access Control	Yes
SNMP	v1, v2c
System Logging Local/Remote Syslog	Local/Remote Syslog
SSH	Yes
Web-based Management	HTTP/HTTPS
L3 Management	Yes
Multi-site Management	Yes
Management VLAN	Yes
OTROS	
Certificacion	CE, FCC, RoHS
Contenidos del Paquete	• AC1750 Wireless MU-MIMO Gigabit Ceiling Mount Access Point EAP265 HD • Gigabit Passive PoE Adapter • Power Cord • Mounting Kits • Installation Guide
Requisitos del Sistema	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Linux

Ambiente

- Operating Temperature: 0–40 °C (32–104 °F)
- Storage Temperature: -40–70 °C (-40–158 °F)
- Operating Humidity: 10–90% RH non-condensing
- Storage Humidity: 5–90% RH non-condensing