



TL-SF1008LP

CARACTERÍSTICAS DE HARDWARE

Interface

- 8× 10/100 Mbps RJ45 Ports (Ports 1–4 support 802.3af PoE)

Medios de Red

- AUTO Negotiation
- AUTO MDI/MDIX
- 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)
- EIA/TIA-568 100Ω STP (maximum 100m)
- 100BASE-TX: UTP category 5, 5e cable (maximum 100m)
- EIA/TIA-568 100Ω STP (maximum 100m)

Cantidad de Ventiladores

Fanless

Cerradura de Seguridad Física

Yes

Fuente de Alimentación Externa

External Power Adapter (Output: 53.5 V DC / 0.81 A)

Tasa de Reenvío de Paquete

1.1904 Mpps

Puertos PoE (RJ45)

- Standard: 802.3 af compliant
- PoE Ports: Ports 1–4
- Power Supply: 41 W

Tabla de Dirección Mac

2K

Jumbo Frame

2 KB

Capacidad de Switcheo

1.6 Gbps

Dimensiones (W X D X H)

6.7 × 3.9 × 1.1 in (171 × 98 × 27 mm)

Consumo Máximo de energía

- 2.2 W (220 V/ 50 Hz. no PD connected)

Disipación Máxima de Calor

- 47.1 W (220 V/ 50 Hz. with 41 W PD connected)
- 7.5 BTU/h(no PD connected)
- 160.61 BTU/h(with 41 W PD connected)

CARACTERÍSTICAS DE SOFTWARE

Método de Transmisión

Store-And-Forward

Funciones Avanzadas

- Compatible With IEEE 802.3af Compliant PDs
- Extend Mode Button (Ports 1–4)

OTROS

Certificacion

Contenidos del Paquete

Ambiente

- Priority Mode Button (Ports 1–2)
 - Mac Address Auto-Learning and Auto-Aging
 - IEEE802.3x Flow Control for Full-Duplex Mode and Backpressure for Half-Duplex Mode
- FCC, CE, RoHS
- TL-SF1008LP
 - Power Adapter
 - Installation Guide
 - Operating Temperature: 0–40 °C (32–104 °F)
 - Storage Temperature: -40–70 °C (-40–158 °F)
 - Operating Humidity: 10–90% RH non-condensing
 - Storage Humidity: 5–90% RH non-condensing