



RE450



CARACTERÍSTICAS DE HARDWARE

Tipo de Enchufe

Estándares y Protocolos

Interface

Botón

Consumo de Energía

Dimensiones (W X D X H)

Antena

CARACTERÍSTICAS INALÁMBRICAS

Frecuencia

Tasa de Señal

Sensibilidad de Recepción

Modos Inalámbricos

Funciones Inalámbricas

Seguridad Inalámbrica

EU, UK, US, AU, KR, JP

IEEE802.11ac, IEEE 802.11n, IEEE 802.11g, IEEE 802.11b

1 x 10/100/1000M Ethernet Port (RJ45)

WPS Button, Reset Button, LED Button, Power Button

10W (max power consumption)

6.4 x 3.0 x 2.6 in. (163 x 76.4 x 66.5mm)

3 x external

2.4GHz & 5GHz(11ac)

5GHz:Up to 1300Mbps

2.4GHz:Up to 450Mbps

5GHz :

11a 6Mbps:-93dBm@10% PER

11a 54Mbps: -76dBm@10% PER

11ac HT20 mcs8: -68dBm@10% PER

11ac HT40 mcs9: -64dBm@10% PER

11ac HT80 mcs9: -61dBm@10% PER

2.4GHz

11g 54M: -77dBm@10% PER

11n HT20 mcs7: -73dBm@10% PER

11n HT40 mcs7: -70dBm@10% PER

Range Extender/Access Point

Wireless Statistic

Concurrent Mode Boost Both 2.4G/5G WiFi Band

Access Control

LED Control

Domain Login Function

Wi-Fi Coverage

64/128-bit WEP

Potencia de Transmisión	WPA-PSK / WPA2-PSK <20dBm(2.4GHz) <23dBm(5GHz)
OTROS	
Certificación	CE, FCC, RoHS
Contenidos del Paquete	AC1750 Wi-Fi Range Extender RE450 Quick Installation Guide
Dimensiones de la Caja (W X D X H)	7.9 x 4.9 x 3.4in. (202x 125 x 86mm) Microsoft® Windows® 98SE, NT, 2000, XP, Vista or Windows 7, 8, 10, Mac® OS, NetWare®, UNIX® or Linux.
Requisitos del Sistema	
Ambiente	Operating Temperature: 0°C~30°C (32°F~86°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

