



Make It Yours.

RISER CABLE PCIe 3.0 X16 VER. 2 - 200MM

MCA-U000C-KPCI30-200

FLEX YOUR GRAPHICS MUSCLE



Flex your Graphics Muscle

The Cooler Master Riser Cable PCIe 3.0 x16 Ver. 2 - 200mm comes revised for maximum flexibility and durability. High quality plastics grant increased cable flexibility and strength for the tightest PCI card installations, while the heavy-duty shielding prevents electromagnetic interference from degrading signal quality. A stainless steel PCI slot adds extra rigidity to the riser to support even the largest and heaviest graphics cards. The IPC4101D compliant PCB provides the best in class performance under high thermal loads and cable flex than any of the non-compliant competitor riser cables in the market.

FEATURES

Ultra Durable PCB:

The IPC4101D compliant PCB provides the best in class performance under high thermal loads, cable flex, and moisture resistance than any of the non-compliant competitor riser cables in the market.

Heavy duty shielding:

EMI shielded 28/30 AWG copper wires ensure minimal signal delay and electromagnetic interference-free operation.

Gold pin connections:

Gold PCI pins allow maximum electrical conductivity with a rated 110g of insertion force per contact pair for high durability.

Protective ABS casing:

UV resistant ABS casing protects cable connection points from rough handling.

Stainless steel-reinforced PCI slot:

Nickel-plated stainless steel PCI slot adds rigidity for superior card retention for even the heaviest PCI card installations.

Ultra-flexible cable sleeves:

TPE cable sleeves allow for maximum flexibility and durability for the tightest cable routing jobs.

SPECIFICATIONS & PACKING INFORMATION

Product Number	MCA-U000C-KPCI30-200
Product Name	Riser Cable PCIe 3.0 x16 Ver. 2 - 200mm
Units per package	1 piece per package
Available color	Black
Compatibility	PCI-E 3.0
Certifications	EMI, IPC4101D/21
Component Materials	PCBA, Copper Wire 28 AWG, Copper Wire 30 AWG
Insulation Materials	PE, TPE
Other Materials	ABS, Stainless Steel, Nickel, Gold, Brass
Connectors	PCI-E x16 Male to PCI x16 90° Female
Cable Length	200mm (7.9in)
Contact Current Rating	1.1A per contact pin
Operating Temperature	-20° to +100° Celsius
Net Weight	90g
Gross Weight	290g
Warranty	1 year

EAN code	4719512101520
UPC code	884102073823
Carton Net Weight	1.80 kg (20pcs per carton)
Carton Gross Weight	6.41 kg
Retail box dimension (L x W x H)	243mmx155mmx23mm
Carton dimension (L x W x H)	360mmx257mmx350mm

Cont.	W/ Pallet	Carton/ Pallet	W/O Pallet
20'	12320	56
40'	24640	56
40 HQ	29040	66