

FLOW TO PRESSURE





Optimized Flow and Pressure

Continuing the SickleFlow 120 series , Cooler Master introduces a few new models with brand new upgraded design features for enhanced performance. Introducing addressable RGB lighting more vibrant than before and certified compatible with all major motherboard manufacturers.

The new SickleFlow 120 fan blades were created with larger blades and increased curvature to optimize the air flow and air pressure performance. Strengthen structural frame design with added rib housing for durability. Improved dustproof and oil leakage prevention for beater life expectancy,

SPECIFICATIONS

Product Name SickleFlow 120 ARGB White Edition Product Number MFX-B2DW-18NPA-R1 Profil Addressable RGB Rifle **Bearing Type** 650~1800 RPM ± 10% Fan Speed (RPM) Airflow (CFM) 62 CFM ± 10% 2.5 mmH₂O ± 10% Air Pressure (mmH2O) 8~27 dBA Fan Noise Level (dBA) Dimensions (mm) 120 x 120 x 25 (4.7 x 4.7 x 1") MTTF (hours) 160,000 3-Pin ARGB **RGB** Connector 5 VDC **RGB** Rated Voltage **RGB Rated Current** 0.21 A 12 VDC Rated Voltage Rated Current 0.15 A Safety Current 0.37A Power Consumption 1.8 W 4-Pin PWM Connector Weight 156 g (0.34 lbs) Warranty 2 Years

Cont. W/ Pallet Carton/ Pallet W/O Pallet 20′ 15840 72 N/A 40' 31680 72 N/A N/A 40 HQ 34320 78

FEATURES

New Air Balance Blade - Optimized fan blade design with increased curvature that improves air flow and air pressure.

Improved Frame Durability - Enhanced square frame structure with added rib-support for reducing turbulent flow, noise and increasing overall work efficiency.

New Bearing Sealant – Two-tier sealing mechanism designed to improve dustproof capabilities and prevent lubricant oil leakage for extended life span and performance.

Luminescent Light Effect– Using milky white tinted fan blades to enhance light dispersion for more vibrant and luminescent effect.

Certified Compatible with Asus Aura, ASRock RGB and MSI RGB Motherboards. (Both ARGB and RGB version)

PACKING INFORMATION

EAN code	4719512107010
UPC code	884102079320
Net weight	0.166
Gross weight	0.231
Package dimension (L x W X H)	143 x 32 x 228 mm
Carton dimension (L x W x H)	420 x 375 x 173 mm
Units/CTN	20