

FEATURES

Tri-Loop Addressable RGB Lighting - 24 Addressable RGB LEDs are uniformly arranged around the crystalized loop design with an additional 6 Addressable LEDs on the fan hub.

Silent Driver IC and Cooling Technology - Silent Driver IC with noise reduction technology offers smooth rotation reduced vibration and fan noise delivering quiet performance even at the highest loads.

Radiant Crystalline Lighting Effect – Unique crystallized loop design on both sides of the fan provide maximum light dispersion of the addressable RGB.

Two-Tier Sealing Design – Two-tier sealing design improves dustproof capabilities and prevent lubricant oil leakage for extended life span and performance.

Wide Range of Compatibility - Addressable RGB with certified compatibility for Asus Aura, ASRock RGB and MSI RGB motherboards

PACKING INFORMATION

EAN code	4719512109847	
UPC code	884102082153	
Net weight	0.157	
Gross weight	0.225	
Package dimension (L x W X H)	143 x 32 x 228 mm	
Carton dimension (L x W x H)	420 x 375 x 173 mm	
Units/CTN	20	

Cont.	W/ Pallet	Carton/ Pallet	W/O Pallet
20'	15840	72	N/A
40′	31680	72	N/A
40 HQ	34320	78	N/A

Radiant Crystalline Lighting

Cooler Master is introducing a brand new product to the MasterFan family - MF120 Prismatic. It features a tri-loop Addressable RGB lighting with distinctive crystallization on both sides. The Silent Driver IC also offers a smooth and quiet fan operation using 7-blade fan to deliver strong air pressure at maximum air flow.

The Addressable RGB lighting is even more vibrant with certified compatibility across all major motherboard manufacturers. The two-tier sealing design improves dustproof capabilities and prevent lubricant oil leakage for extended life span and performance.

SPECIFICATIONS

Product Name MasterFan MF120 Prismatic Product Number MFY-B2DN-20NPA-R1 Profile Addressable RGB Bearing Type Rifle Fan Speed (RPM) 650~2000 RPM ± 5% Airflow (CFM) 55 CFM (Max) Air Pressure (mmH2O) 2.91 mmH2O (Max) Fan Noise Level (dBA) 8~27 dBA Dimensions (mm) 120 x 120 x 25 (4.7 x 4.7 x 1") MTTF (hours) 160,000 RGB Connector 3-Pin ARGB RGB Rated Voltage 5 VDC RGB Rated Current 0.65 A Rated Voltage 12 VDC Rated Current 0.12 A Safety Current 0.37A Power Consumption 1.44 W Connector 4-Pin PWM Weight 153 g (0.34 lbs) Warranty 2 Years		
Profile Addressable RGB Bearing Type Rifle Fan Speed (RPM) 650~2000 RPM ± 5% Airflow (CFM) 55 CFM (Max) Air Pressure (mmH2O) 2.91 mmH2O (Max) Fan Noise Level (dBA) 8~27 dBA Dimensions (mm) 120 x 120 x 25 (4.7 x 4.7 x 1") MTTF (hours) 160,000 RGB Connector 3-Pin ARGB RGB Rated Voltage 5 VDC RGB Rated Current 0.65 A Rated Voltage 12 VDC Rated Current 0.12 A Safety Current 0.37A Power Consumption 1.44 W Connector 4-Pin PWM Weight 153 g (0.34 lbs)	Product Name	MasterFan MF120 Prismatic
Bearing Type Rifle Fan Speed (RPM) 650~2000 RPM ± 5% Airflow (CFM) 55 CFM (Max) Air Pressure (mmH2O) 2.91 mmH2O (Max) Fan Noise Level (dBA) 8~27 dBA Dimensions (mm) 120 x 120 x 25 (4.7 x 4.7 x 1") MTTF (hours) 160,000 RGB Connector 3-Pin ARGB RGB Rated Voltage 5 VDC RGB Rated Voltage 12 VDC Rated Voltage 12 VDC Rated Current 0.12 A Safety Current 0.37A Power Consumption 1.44 W Connector 4-Pin PWM Weight 153 g (0.34 lbs)	Product Number	MFY-B2DN-20NPA-R1
Fan Speed (RPM) 650~2000 RPM ± 5% Airflow (CFM) 55 CFM (Max) Air Pressure (mmH2O) 2.91 mmH2O (Max) Fan Noise Level (dBA) 8~27 dBA Dimensions (mm) 120 x 120 x 25 (4.7 x 4.7 x 1") MTTF (hours) 160,000 RGB Connector 3-Pin ARGB RGB Rated Voltage 5 VDC RGB Rated Current 0.65 A Rated Voltage 12 VDC Rated Current 0.12 A Safety Current 0.37A Power Consumption 1.44 W Connector 4-Pin PWM Weight 153 g (0.34 lbs)	Profile	Addressable RGB
Airflow (CFM) 55 CFM (Max) Air Pressure (mmH2O) 2.91 mmH2O (Max) Fan Noise Level (dBA) 8~27 dBA Dimensions (mm) 120 x 120 x 25 (4.7 x 4.7 x 1") MTTF (hours) 160,000 RGB Connector 3-Pin ARGB RGB Rated Voltage 5 VDC RGB Rated Current 0.65 A Rated Voltage 12 VDC Rated Current 0.12 A Safety Current 0.37A Power Consumption 1.44 W Connector 4-Pin PWM Weight 153 g (0.34 lbs)	Bearing Type	Rifle
Air Pressure (mmH2O) 2.91 mmH2O (Max) Fan Noise Level (dBA) 8~27 dBA Dimensions (mm) 120 x 120 x 25 (4.7 x 4.7 x 1") MTTF (hours) 160,000 RGB Connector 3-Pin ARGB RGB Rated Voltage 5 VDC RGB Rated Current 0.65 A Rated Voltage 12 VDC Rated Current 0.12 A Safety Current 0.37A Power Consumption 1.44 W Connector 4-Pin PWM Weight 153 g (0.34 lbs)	Fan Speed (RPM)	650~2000 RPM ± 5%
Fan Noise Level (dBA) 8~27 dBA Dimensions (mm) 120 x 120 x 25 (4.7 x 4.7 x 1") MTTF (hours) 160,000 RGB Connector 3-Pin ARGB RGB Rated Voltage 5 VDC RGB Rated Current 0.65 A Rated Voltage 12 VDC Rated Current 0.12 A Safety Current 0.37A Power Consumption 1.44 W Connector 4-Pin PWM Weight 153 g (0.34 lbs)	Airflow (CFM)	55 CFM (Max)
Dimensions (mm) 120 x 120 x 25 (4.7 x 4.7 x 1") MTTF (hours) 160,000 RGB Connector 3-Pin ARGB RGB Rated Voltage 5 VDC RGB Rated Current 0.65 A Rated Voltage 12 VDC Rated Current 0.12 A Safety Current 0.37A Power Consumption 1.44 W Connector 4-Pin PWM Weight 153 g (0.34 lbs)	Air Pressure (mmH2O)	2.91 mmH ² O (Max)
MTTF (hours) 160,000 RGB Connector 3-Pin ARGB RGB Rated Voltage 5 VDC RGB Rated Current 0.65 A Rated Voltage 12 VDC Rated Current 0.12 A Safety Current 0.37A Power Consumption 1.44 W Connector 4-Pin PWM Weight 153 g (0.34 lbs)	Fan Noise Level (dBA)	8~27 dBA
RGB Connector 3-Pin ARGB RGB Rated Voltage 5 VDC RGB Rated Current 0.65 A Rated Voltage 12 VDC Rated Current 0.12 A Safety Current 0.37A Power Consumption 1.44 W Connector 4-Pin PWM Weight 153 g (0.34 lbs)	Dimensions (mm)	120 x 120 x 25 (4.7 x 4.7 x 1")
RGB Rated Voltage 5 VDC RGB Rated Current 0.65 A Rated Voltage 12 VDC Rated Current 0.12 A Safety Current 0.37A Power Consumption 1.44 W Connector 4-Pin PWM Weight 153 g (0.34 lbs)	MTTF (hours)	160,000
RGB Rated Current 0.65 A Rated Voltage 12 VDC Rated Current 0.12 A Safety Current 0.37A Power Consumption 1.44 W Connector 4-Pin PWM Weight 153 g (0.34 lbs)	RGB Connector	3-Pin ARGB
Rated Voltage 12 VDC Rated Current 0.12 A Safety Current 0.37A Power Consumption 1.44 W Connector 4-Pin PWM Weight 153 g (0.34 lbs)	RGB Rated Voltage	5 VDC
Rated Current 0.12 A Safety Current 0.37A Power Consumption 1.44 W Connector 4-Pin PWM Weight 153 g (0.34 lbs)	RGB Rated Current	0.65 A
Safety Current 0.37A Power Consumption 1.44 W Connector 4-Pin PWM Weight 153 g (0.34 lbs)	Rated Voltage	12 VDC
Power Consumption 1.44 W Connector 4-Pin PWM Weight 153 g (0.34 lbs)	Rated Current	0.12 A
Connector 4-Pin PWM Weight 153 g (0.34 lbs)	Safety Current	0.37A
Weight 153 g (0.34 lbs)	Power Consumption	1.44 W
	Connector	4-Pin PWM
Warranty 2 Years	Weight	153 g (0.34 lbs)
	Warranty	2 Years